

Xitech's DNAPL Pumps

DNAPL Recovery Pump

This **2" Smart Pump** was designed to recover low viscosity DNAPLs like TCE. The **2" Smart Pump** is completely resistant to all solvents, easily fits into a 2" schedule 40 well or larger, has a pumping rate up to 12 GPH, operating well depth of 200 feet, and requires no above ground controls to operate. Maximum air requirements are .5 CFM @ 125 PSIG, and air quality requirements are 5-10 Microns.



U.S. Patent # 5,326,458

Model ADJ201

Pumping range: .1 GPH - 12 GPH
Size: 1.8" diameter x 9 inches long
Weight: 3 pounds

DNAPL Recovery Pump

This **4" Smart Pump** was designed to recover high viscosity DNAPLs like Coal-Tar. The **4" Smart Pump** is completely resistant to all solvents, easily fits into any 4" well or larger, has a pumping rate up to 60 GPH, operating well depth of 200 feet, and requires no above ground controls to operate. The maximum air requirements are .5 CFM @ 125 PSIG, and air quality requirements are 5-10 Microns.



U.S. Patent # 5,326,458

Model ADJ1100

Pumping range: .1 GPH - 60 GPH
Size: 3.5" diameter x 9 inches long
Weight: 8 pounds

www.xitechinc.com

toll free
888-867-9483