

Xitech's Flow Totalizer

The **Xitech Flow Totalizers** are a great solution for keeping track of individual well production. These **Totalizers** have the perfect flow range for our skimmers and pumps, great accuracy, and material construction for light floating product removal. The **Model 100-5 Totalizer** includes an air eliminator device for use with our 2" skimmers. The air eliminator removes all air from the liquids being discharged from the well. Removing the air makes the

Totalizer readings more accurate. The **Model 100 Totalizer** is to be used with our 4" skimmers. All of the 4" skimmers come with a built-in air eliminator feature. The **Model 100** can be used with our 2" and 4" pumps. These **Totalizers** do not require any electrical power, include a custom mounting bracket for easy servicing, and a low pressure check valve to prevent any back flow. These **Totalizers** come with the 1/2" tubing fittings on the inlet and outlet.



Model 100 (for 2" Skimmers)
Order No. 100



Model 100-5
(for 4" Skimmers, 2" Pumps, and 4" Pumps)
Order No. 100-5



Model 100 and 100-5 Specifications

No Electrical power required

Acceptable media: Light fuel oils
Flow range: 0.25 GPH to 20 GPH
Accuracy: $\pm 1\%$

Maximum count: 999,999.99 gallons
Minimum flow rate: 0.25 GPH
Maximum temperature: 140 degrees F
Maximum operating pressure: 150psi
Smallest readable scale: 0.001 gallon
Measurement method: Positive displacement

toll free 888-867-9483

www.xitechinc.com